

08CH 系列贴片压敏电阻

Model Number	Working voltage (MAX)		Breakdown Voltage	Peak Current(MAX)	Clamping Voltage(MAX)		Energy Absorption(MAX)	Typical Capacitance
Unit Condition	AC (VRMS)	DC (V)	1mA (V)	8/20uS (A)	(A)	(V)	10/1000 (J)	1KHz (pF)
08CH560K	35	45	56	250	5	106	2.3	530
08CH680K	40	56	68	250	5	124	3.0	360
08CH121K	75	102	120	500	10	198	6.0	200
08CH201K	130	175	200	500	10	340	13.0	100
08CH361K	230	300	360	500	10	593	19.0	45
08CH431K	250	369	430	450	10	705	19.0	39
08CH471K	300	385	470	400	10	775	18.0	35
Notes: 1.Tolerance of breakdown voltage: $\pm 10\%$ 。 2.Tolerance of capacitance Voltage: $\pm 20\%$ 。 3. Typical leakage at 25℃ < 50uA, maximum leakage 100uA 。 4. In order to satisfy the applications of customer in various fields, the capacitance range ※ can be designed during manufacturing according to the request, please contact our sales department if needed 。								

Dimensions

Model	2220 (5750)	08CH
Length(L)	5.70 ± 0.20	8.10 ± 0.30
Width(W)	5.00 ± 0.20	5.00 ± 0.30
Thickness(D)	2.50max	2.50max

